# **SPECIFICATIONS**

Model	A1 1" A1 2"
Distance Measurement (Reflector)	1.22
Range	5000m
	1000m
Accuracy	±(1+1×10 <sup>-6</sup> ·D)mm ±(2+2×10 <sup>-6</sup> ·D)mm
Measure Time	Continuous: 0.35s, Tracking: 0.2s, Single: less than 1.2s
Distance Measurement (Reflectorless)	
Range (Kodak Standard Gray, 90% Diffuse Reflectance)*	1000m
Accuracy	0-300m 3+2 300-600m 5+2 >600m 10+2
Measure Time	Continuous: 0.35s, Tracking: 0.2s, Single: less than 1.2s
Angle Measurement	
Detection Method	Absolute Encoding
Diameter of Encoding Disk	79mm
Min. Reading	0.1"/1" 1"
Accuracy	1" 2"
Telescope	
Image	Erect
Tube Length	152mm
Effective Aperture	Effective: 45mm DTM: 47mm
Magnification	30X
Field of View	1°30'
Resolution	3"
Min. Focusing Range	1.5m
Comprehensive parameter	
Sensor	Dual-axis Liquid-Electric Sensor (Range: ±3', Accuracy: 1")
Atmospheric Correction	T-P Sensor Auto Correction
Prism Constant	Auto Correction
Trigger	Under Battery House
IP Standard	IP55
Vial	
Plate Vial	30"/2mm
Circular Vial	8'/2mm
Plummet	Laser Plummet (Optical Optional)
Data Transfer	RS-232C, USB, BLUETOOTH, Flash Disk
Display Unit	100 0 11
Туре	LCD, Graphic
Size	5.0 Inch
Graphic Display	Max: 99999999.999 Min: 0.1mm Max: 99999999.999 Min:1mm
Battery	1911 0 0
Power Supply	Lithium Battery
Voltage	7.4V
Working Hours  Dimention And Weight	8 Hours
Dimention And Weight  Dimention	206v200v252
Weight	206x200x353mm
-	6.0kgs
Storage	2200
ROM RAM	32GB
Function	3GB
GPS	Available
	Available
Voice Recording CPU	
Data And Network	mt6735
Data Transfer	BLUETOOTH, Wifi, Wifi Hotspot
4G	Available
3G/2G	Available
System Version (Sep.2018)	
System version (Sep.2018)	Android 9.0

<sup>\*©</sup> South Surveying & Mapping Technology CO.,LTD All Rights Reserved



SOUTH SURVEYING & MAPPING TECHNOLOGY CO., LTD.

Add: South Geo-information Industrial Park, No. 39 Si Cheng Road, Tian He IBD, Guangzhou 510663, China Tel: +86-20-23380888 Fax: +86-20-23380800

E-mail: mail@southsurvey.com export@southsurvey.com impexp@southsurvey.com euoffice@southsurvey.com http://www.southinstrument.com







## **Features**















The first Android Total Station A1 features open interface, available for any 3rd party software Available for customized software based on your own request

5.0 Inch capacitive screen with multi-touch technology, quick and smooth for operations.

## Hardware

# Intergrated CPU



MTK MT6735 4-core processor boosts speed, responsiveness and performance 64 digits Cortex-A53 MPCORE TM structure, in 1.3GHz frequency



# **Enhanced algorithm**

Powerful GPU with MALIT720-MP2 3D processor

## WIFI/4G Network

Compatible with the main network system in worldwide, available for SIM card



### **Multiple Transfer**

Standard Bluetooth, WIFI, Hotspot, RS232C, USB connection

### Structure Improved



Stable: Horizontal co-axis, improved the stability of accuracy

Dual-Compensator: Re-located at the vertical center

## Software

## simple but not simplistic

# **Professional Framing**

Iconic user interface, offers a smooth and flashing working experience. Behind every simple step on A1 is our unremitting efforts to optimized the algorithm.

# **Built-in Toolbar, Quicker Than Ever**

Integrate the setting page of laser pointer and plummet switch into quick menu. The switching of measure mode, target and sensor becomes quicker to activate in toolbar than the other models.

### **Stake-out Guidance**

Compass pointer with stake-out sketch, driving the new premium extras and powerful tools for your job.

A1 considered all the possible request by summing up the user's feedback over the years.

## **Automatic Graph Drawing**

The graphic drawing in A1 realizes the data viewing and outputs in real-time. Precision designed down to the last pixel in all conditions.









## **Functions**



MLM

Angle Offset



Resection

Distance Offset



















