SPECIFICATIONS

	KTS-442UT
Measuring Range	
1P	5.0km
3P	8-10 km
Non prism	1000m (1500m optional)
Digital Display	Maximum: 99999999999999999999999999999999999
Accuracy	With prism: 2mm+2ppm, without prism 3mm+2ppm
Measuring Time	Tracking 0.1s, Fine 0.3s (optimal)
Atmospheric Correction	Automatic Correction by Inputting Parameter
Prism Constant	Automatic Correction by Inputting Parameter
Angle Measurement	
Measurement Method	Absolute Encoding
Diameter of The Raster Disk	79mm
Minimum Reading	1 " / 5 " Optional
Accuracy	2 "
Detection Method	Horizontal: Four Sensors Vertical: Four Sensors
Telescope	
Image	Erect
Length	154mm
Effective Aperture	45mm (DTM 50mm)
Magnification	30 X
Field of View	1° 30′
Resolving Power	3 "
Minimum Focus	lm
Compensation	
System	Dual axis liquid-electric
Working Range	±3′
Resolving Power	1 "
Sensitivity of Vials	
Plate Vial	30 " /2mm
Circular Vial	8' /2mm
Laser Plummet	Yes
Data Storage and Communication	
Internal Memory	12MB (up to 100,000 points)
External Memory	USB Flash Disk (up to 256 GB)
Communication Port	USB, Bluetooth
Display	
Туре	Dual sides, 6 lines, black and white
Battery	
Power Supply	Rechargeable battery (3100mAH)
Voltage	7.4V DC
Operation Time	10 hours
Dimension and Weight	
Dimension	160mm×150mm×330mm
Weight	5.7 kg
Environmental Specification	
Dust/Water (IEC60529)	IP66
Working Temperature Range	-20℃~50℃
Humidity	95%, non-condensing
,	



GUANGDONG KOLIDA INSTRUMENT CO., LTD.

Add: 7/F, South Geo-information Industrial Park, No.39 Si Cheng Road, Tian He IBD, Guangzhou 510663, China Tel: +86-20-22139033 Fax: +86-20-22139032 Email: export@kolidainstrument.com market@kolidainstrument.com http://www.kolidainstrument.com

KTS-442UT

The High Performance Total Station with Great Reliability, Flexibility and Economy





Kolida's Vision and Mission:

Delivering more values to global users by providing sustaining innovation and uncompromising quality



Welcome to Kolida Instrument, a fusion of passionate people, continuously innovated technology, services, as well as 25 years experience of manufacturing total station.

Every year more than 12,000 customers choose to purchase Kolida total stations. To ensure our instruments meet the high precision and quality requirement of global users, we manufacture them in state-of-the-art facilities around China.

We recognize certain employees as Master Craftspersons, exceptionally skilled people who take charge of manufacturing the parts of products that require extremely high precision and quality. Their Fast, accurate work creates uniform products of superb quality.

In addition to introducing the latest manufacturing facilities and technologies, we are shortening manufacturing lead times and reducing costs by reviewing production processes and innovating Procurement, to offer you a good instrument as affordable as possible.

You demand, our mission.

Seven Major Improvements

To lift your capability and productivity

TECHNOLOGIES



1000/1500m Reflectorless



Ultra Fast





Ultra Low-noise Amplifier



Noise Phase Analysis





USB Flash





Dual Axis





Laser Pointing



PROGRAMS















Distance Offset









Video and Article: http://www.kolidainstrument.com/product/details/id/81.html